



Highlights:

- 2.5-way in-wall loudspeaker system designed for on-axis listening as LCR and surround channels
- 1-inch 2410H-2 compression driver tweeter mated to a JBL patented High-Definition Imaging (HDI™) horn precision molded baffle assembly
- Four 5.25-inch (130mm) Advanced Aluminum Matrix cone cast frame woofers
- Can be mounted vertically or horizontally
- Patented Cat Claw installation mechanism
- Gold plated, spring-loaded binding posts
- Includes paintable zero-bezel, magnetically attached grilles
- Compatible with WB54 pre-construction bracket

General Specifications:

- ► Type: 2.5-way in-wall loudspeaker
- Low Frequency Driver: Four 5.25" (130mm) advanced Aluminum Matrix cone cast-frame woofers (JW13AI-4)
- ► High Frequency Driver: 1" (25mm) 2410H-2 Teonex® annular ring-diaphragm compression driver
- ► Recommended Amplifier Power: 25 200W RMS
- ► Impedance: 4 Ohm
- ► Loudspeaker Sensitivity: 91dB/2.83V/1m (2pi anechoic)
- ► Frequency Response: 50Hz 30kHz (-6dB on-axis), 2pi anechoic
- Crossover Frequency: 1.8kHz
- ► High Frequency Coverage Angle (-6dB): 80° Vertical/80° Horizontal, from 2kHz to 17kHz
- ► Enclosure Type: Open back
- ► Controls: Boundary Proximity Control
- ► Grille Dimensions: 7.29" (185mm) x 31.32" (796mm)
- ► Product Dimensions (with grille): 7.29" (185mm) x 31.32" (796mm) x 3.82" (97.1mm)
- ► Cut-out Dimensions: 30 18" (766mm) x 6 18" (157mm)
- ► Rough-in Bracket: WB54
- ► Mounting Depth: 3.63" (92mm)
- ► Input Type: Gold-plated spring-loaded binding posts
- ► Product Weight: 22.2 lbs (10.07kg)
- ► Shipping Weight: 25.6 lbs (11.61kg)
- ► Shipping Units of Measure: Each
- ▶ Warranty: 5 Years







